

FULL MATRIX GRAPHIC COUNT DOWN TIMER

Model : GCDT 01

MPN: 2100004476



FULL MATRIX GRAPHIC COUNT DOWN TIMER

CPU Micro Controller

Mechanical Specifications

Structural Material Polycarbonate strengthen against UV rays
Body Color Light Grey/Black
Dimensions 360mm x 370mm x 220mm

Display Specification

Lamp Diameter 300mm
Digit Height 150 -165mm
Height of Man 150-190mm
Display Type Full Matrix Graphic, Dual Colored (Red & Green)
No. of Digit 3

LED Specifications

LED Diameter 5mm
LED Viewing Angle 30°

LED Wave Length 630-640nm (Red)
505nm - 520nm (Blue-Green)
LED Dice Material AlInGap (Red), InGaN (Blue-Green)
LED Life Time 1,00,000 hrs from the date of commissioning

Technical Features

Power Consumption 20 - 30 Watt Per Lamp
Input Power 85-260V AC, 50Hz
Operating Temperature . -20 to + 60 °C
Humidity 0% to 95% Relative Humidity

Standard EN12966

Model : GCDDT 01

MPN: 2100004476



CMS COMPUTERS LTD.

70, LAKE ROAD
BHANDUP WEST, MUMBAI 400 078

TEL: (91-22) 41259000
FAX: (91-22) 41259001 E-mail : cmstlshq@cms.co.in
Web Site : www.cms.co.in

FULL MATRIX GRAPHIC COUNT DOWN TIMER

Working of Countdown Timer

Graphic Count Down Timer is configurable in two modes

Vehicular Mode & Pedestrian Mode

The Vehicular countdown timer would be dual colour,

- **Red** for **STOP** or **STP**
- **Green** Colour for **GO**.

These would alternate Red and Balance Phase Time for **STOP** or **STP** in flashing.

Alternate Green and Balance Phase Time for **GO** in flashing.

The Pedestrian Countdown timer would be dual color

- **RED MAN** & balance phase time
- **GREEN MAN** & balance phase time in flashing.



CMS COMPUTERS LTD.

70, LAKE ROAD
BHANDUP WEST, MUMBAI 400 078

TEL: (91-22) 41259000

FAX: (91-22) 41259001 E-mail : cmstlshq@cms.co.in

Web Site : www.cms.co.in